

# 9.8 HP

<b>Engine Model (Color)</b>	(a) E10RG4 Graphite (b) E10RGL4 Graphite (c) E10TPL4 Graphite (d) E10PGL4 Graphite
<b>Engine Type</b>	2-cylinder
<b>Bore x Stroke - in (mm)</b>	2.17 x 1.73 (55 x 44)
<b>Displacement - cu in (cc)</b>	12.8 (209)
<b>Gear Ratio</b>	2.08:1
<b>Full Throttle RPM Range</b>	5000-6000 RPM
<b>Weight - lbs (kg)*</b>	(a) 81.5 (37) (b) 84 (38) (c) 102.5 (46) (d) 103.6 (47)
<b>Starting</b>	(a)(b) Rope (c)(d) Electric
<b>Controls</b>	(a)(b)(c) Tiller Handle (d) Mechanical
<b>Fuel Induction</b>	Carbureted
<b>Alternator Output</b>	Only on Electric Models: 12V, 145W, 6A (Standard on Electric Start Models)
<b>Steering</b>	(a)(b)(c) Tiller (d) Remote
<b>Trim Method</b>	(a)(b) Manual (c) Manual or Power (d) Power Tilt
<b>Shaft Length - in (mm)</b>	(a) 15 (381) (b)(c)(d) 20 (508)
<b>Oil Tank Capacity - fl oz (ml)</b>	27 (800)
<b>Recommended Oil</b>	Evinrude/ Johnson 5W40 Ultra 4-Stroke Oil
<b>Recommended Fuel</b>	87 Octane
<b>Warranty</b>	3-Year, Non-Declining
<b>Emissions Compliance</b>	EPA 2013 / CARB 3 STAR
<b>Recommended Fuel</b>	87 Octane
<b>Warranty</b>	3-Year, Non-Declining
<b>Emissions Compliance</b>	EPA 2013 / CARB 3 STAR / European Union

